V-FASTR: COMMENSAL TRANSIENT DETECTION WITH THE VLBA

Walter Brisken¹, Adam Deller^{1,2}, Walid A. Majid³, David R. Thompson³, Steven Tingay⁴, Kiri L. Wagstaff³, and Randall Wayth⁴

- ¹National Radio Astronomy Observatory
- ²University of California, Berkeley
- ³Jet Propulsion Laboratory, California Institute of Technology
- ⁴ICRAR/Curtin University


Contact: kiri.wagstaff@jpl.nasa.gov



Research described in this presentation was carried out in part at the Jet Propulsion Laboratory under a JPL Research and Technology Development Grant. Images are provided courtesy NASA / Caltech JPL / Curtin University / NRAO. Copyright 2011. All Rights Reserved. Government sponsorship acknowledged.

Why fast radio transients?

- Excellent probes of ISM, IGM via dispersion measure (DM) and rotation measure (RM)
 - Laboratories of compact sources, extreme astrophysics
- Known sources and targets
 - Intermittent pulsars (RRATs), giant pulses, merging neutron stars
- Exotic sources
 - Black hole evaporation
 - Gravitational wave events
 - Extra-terrestrial intelligence?
 - Etc.




[Lorimer et al., 2007]

Largely unexplored space. New discoveries await!

Very Long Baseline Array

- 10 25-m dishes
- Data recorded to disk at each telescope, shipped to Array Operations Center in Socorro for correlation




- Correlation by DiFX software correlator [Deller et al., 2007]
 - Software correlators are flexible!
 - Can get autocorrelations with short integration times (1 ms),
 virtually for free (nothing's for free)

V-FASTR: FASt TRansient Detection


- Trailblazer for CRAFT survey science project for ASKAP
- Goal: continuously detect fast (< 5s) radio transients
 - Commensal detection: Analyze VLBA filterbank data in real-time as it flows through the DiFX software correlator
 - Minimal impact to correlator operations
 - Detect transients even in campaigns with other observing goals
- Fast "trigger" decision to save buffer for offline analysis
 - Dramatically reduce data volume for next stage of analysis
- Innovations
 - Adaptive behavior using injected (known) pulses
 - Machine learning for multi-station detection and RFI excision
- Now running 24/7 on all VLBA observations
 - Detections to be shared with PIs first

V-FASTR Architecture



Example VLBA Data

- Pulsar B0329+54
 - DM 26.8 pc/cm³
 - Period: 714 ms
- VLBA observations
 - 1.4-1.674 GHz
 - 1 ms integration time
 - 9 scans, each lasting 242 s



Robust Summation

Incoherent summation: sum power across all stations

$$\max_{DM} \frac{1}{A} \sum_{a=1}^{A} S_a(DM)$$

Robust summation: omit min and max stations from sum


$$\max_{DM} \frac{1}{A} \sum_{a=1}^{A-1} S_a(DM)$$

Multi-Station Detection

- Learn model of data "background"
- Compute combined estimate that new signal is remote (observed by multiple stations)


$$\max_{DM} \frac{1}{A} \sum_{a=1}^{A} P(X \le S_a(DM))$$

Improves sensitivity over incoherent summation




Machine Learning: Adaptation


- Inject known (synthetic) pulses into data stream
- Adjust detection thresholds to maintain optimal performance



Pulsar B0329+54 Detection Results



Pulsar B0329+54 Sensitivity Results



V-FASTR: Summary

- Now running 24/7 on all VLBA observations
- Value of real-time commensal transient searches
 - Detect events otherwise discarded even for campaigns uninterested in transients
- Machine learning enables better multi-station detection and adaptive detection thresholds
- Testbed for SKA-related concerns
 - Maintain acceptably low false alarm rate, real-time performance
 - Constrain buffer (disk) consumption for detections
 - Value of software correlator
- Raises issues in advance of the SKA
 - What to do with detections? New policies needed?

Thanks to...

- Dayton Jones, Joe Lazio, Bob Preston (JPL)
- JPL, NSF, NRAO, ICRAR (funding)

